

海運材積單位換算: 1立方公尺(CBM)(M³)=35.315英材(立方英尺)(CU.FT), 1英材(立方英尺)(CU.FT)=1728立方英吋(CU.IN)																	
貨櫃類別	外部尺寸			內部尺寸			重量限制			櫃門內徑							
	長	寬	高	長	寬	高	總重	空櫃重	貨物淨重	內容積	寬	高					
20呎鋼製乾貨貨櫃	6.058m (20'-0")	2.438m (8'-0")	2.591m (8'-6")	5.898m (19'-4 13/16")	2.352m (7'-8 19/32")	2.385m (7'-9 57/64")	24,000kg (52,910 lb)	2,330kg (5,140 lb)	21,670kg (47,770 lb)	33.1cbm (1,169cu.ft)	2.343m (7'-8 1/8")	2.280m (7'-5 3/4")					
總重為 30,480 KG 之 20呎貨櫃櫃號始於 EMCU 3204073 及 EISU 3568118。																	
40呎鋼製乾貨貨櫃	12.192m (40'-0")	2.438m (8'-0")	2.591m (8'-6")	12.032m (39'-5 45/64")	2.352m (7'-8 19/32")	2.385m (7'-9 57/64")	30,480kg (67,200 lb)	4,000kg (8,820 lb)	26,480kg (58,380 lb)	67.5cbm (2,385cu.ft)	2.343m (7'-8 1/8")	2.280m (7'-5 3/4")					
上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。																	
40呎超高鋼製乾貨貨櫃	12.192m (40'-0")	2.438m (8'-0")	2.896m (9'-6")	12.032m (39'-5 45/64")	2.352m (7'-8 19/32")	2.69m (8'-9 15/16")	30,480kg (67,200 lb)	4,200kg (9,260 lb)	26,280kg (57,940 lb)	76.2cbm (2,690cu.ft)	2.343m (7'-8 1/8")	2.585m (8'-5 49/64")					
上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。																	
45呎超高鋼製乾貨貨櫃(1)	13.716m (45'-0")	2.438m (8'-0")	2.896m (9'-6")	13.556m (44'-5 7/10")	2.352m (7'-8 19/32")	2.698m (8'-10 17/64")	30,480kg (67,200 lb)	4,800kg (10,580 lb)	25,680kg (56,620 lb)	86.1cbm (3,040cu.ft)	2.340m (7'-8 1/8")	2.585m (8'-5 3/4")					
上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。																	
45呎超高鋼製乾貨貨櫃(2)	13.716m (45'-0")	2.438m (8'-0")	2.896m (9'-6")	13.556m (44'-5 7/10")	2.352m (7'-8 19/32")	2.698m (8'-10 17/64")	30,480kg (67,200 lb)	4,870kg (10,858 lb)	25,610kg (56,342 lb)	86cbm (3,040cu.ft)	2.340m (7'-8 1/8")	2.585m (8'-5 3/4")					
EISU 804001~EISU 804500; EMCU 801001~EMCU 802500																	
45呎超高鋼製乾貨貨櫃(3)	13.716m (45'-0")	2.438m (8'-0")	2.896m (9'-6")	13.556m (44'-5 7/10")	2.352m (7'-8 19/32")	2.698m (8'-10 17/64")	32,500kg (71,650 lb)	4,700kg (10,360 lb)	27,800kg (61,290 lb)	86cbm (3,040cu.ft)	2.340m (7'-8")	2.585m (8'-6")					
EISU 802001~EISU 804000 2. 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。																	
40呎超高成衣櫃	12.19m (40'-0")	2.44m (8'-0")	2.90m (9'-6")	12.03m (39'-5 45/64")	2.35m (7'-8 19/32")	2.69m (8'-9 15/16")	30,480kg (67,200 lb)	4,200kg (9,172 lb)	26,280kg (58,028 lb)		2.343m (7'-8 1/8")	2.585m (8'-5 49/64")					
上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。																	
20呎油槽櫃	6.058m (20'-0")	2.438m (8'-0")	2.591m (8'-6")				6,000kg ³	3,385kg	32,615kg	24,000litres	工作溫度						
上述油槽櫃僅用於集團屬輪上，做為貨櫃式發電機之供油使用，不對外營運。																	
-20°C to 130°C																	
20呎全高開頂貨櫃	6.058m (20'-0")	2.438m (8'-0")	2.59m (8'-6")	5.898m (19'-4")	2.352m (7'-8 1/2")	2.342m (7'-8 1/8")	20,320kg (44,800 lb)	2,200kg (4,850 lb)	18,120kg (39,950 lb)	32.5cbm (1,148cu.ft)							
UGMU 490001~UGMU 490150; EMCU 460261~EMUC 460520; EISU 460001~EISU 460400																	
40呎全高開頂貨櫃	12.192m (40'-0")	2.438m (8'-0")	2.591m (8'-6")	12.034m (39'-5")	2.352m (7'-8 1/2")	2.330m (7'-8 1/8")	30,480kg (67,200 lb)	4,100kg (9,040 lb)	26,380kg (58,160 lb)	65.9cbm (2,327cu.ft)							
EMCU 400362~ 400810; UGMU 407001~ 407050; EISU 400001~ 400600																	
20呎貨櫃式發電機櫃	6.058 (20'-0")	2.438 (8'-0")	2.591 (8'-6")	5.898 (19'-4 13/16")	2.352 (7'-8 19/32")	2.385 (7'-9 57/64")	8,500kg	2,400kg	6,100kg		供電量:450kw						
上述發電機僅用於集團屬輪上，供應冷凍櫃插電使用，不對外營運。																	
插座數:40																	
20呎鋼製冷凍貨櫃	6.058m (20'-0")	2.438m (8'-0")	2.591m (8'-6")	5.500m (18'-17/32")	2.298m (7'-6 15/32")	2.276m (7'-5 39/64")	30,480kg (67,180 lb)	3,020kg (6,700 lb)		28.8cbm (1,016 cu.ft)	設溫之容許誤差						
製冷能力:瓦(千卡)/攝氏(華氏)																	
11,000(9,460)/1.7(35)6,280(5,400)/-18(0)							通風量:立方公尺/小時			0-180		+-0.25C					
10,550(9,073)/2(35)6,150(5,289)/-18(0)										0-240		+-0.25C					
此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。																	
20呎鋁製冷凍貨櫃	6.058m (20'-0")	2.438m (8'-0")	2.591m (8'-6")	5.480m (17'-0")	2.286m (7'-6")	2.235m (7'-3")	24,000kg (52,800 lb)	2,800kg (6,170 lb)		28cbm (989cu.ft)	設溫之容許誤差						
製冷能力:瓦(千卡)/攝氏(華氏)																	
11,000(9,460)/1.7(35)6,280(5,400)/-18(0)							通風量:立方公尺/小時			0-180		+-0.25C					
此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。																	
40呎超高鋼製冷凍貨櫃	12.192m (40'-0")	2.438m (8'-0")	2.896m (9'-6")	11.585m (37'-11 55/64")	2.290m (7'-6 15/32")	2.544m (8'-4 5/32")	34,000kg (74,960 lb)	4,760kg (10,490lb)		67.5cbm (2,384cu.ft)	設溫之容許誤差						
製冷能力:瓦(千卡)/攝氏(華氏)																	
11,000(9,460)/1.7(35)6,280(5,400)/-18(0)							通風量:立方公尺/小時			0-180		+-0.25C					
10,550(9,073)/2(35)6,150(5,289)/-18(0)										0-240		+-0.25C					
此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。																	
40呎超高鋁製冷凍貨櫃	12.192m (40'-0")	2.438m (8'-0")	2.896m (9'-6")	11.563m (37'-11")	2.286m (7'-6")	2.5047m (8'-2")	30,480kg (67,200 lb)	4,300kg (9,480 lb)		66.27cbm (2,340)	設溫之容許誤差						
製冷能力:瓦(千卡)/攝氏(華氏)																	
11,000(9,460)/1.7(35)6,280(5,400)/-18(0)							通風量:立方公尺/小時			0-180		+-0.25C					
此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。																	
20呎角柱可折疊式之床式/平台兩用貨櫃(EMCU760321~EMCU760520)																	
外部尺寸			內部尺寸			重量限制			外部尺寸			內部尺寸			重量限制		
長	寬	高	長	寬	高	總重	空櫃重	貨物淨重	長	寬	高	長	寬	高	總重	空櫃重	貨物淨重
6.058 m (20'-0")	2.438 m (8'-0")	2.591 m (8'-6")	5.650 m (18'-6 7/16")	2.030 m (6'-7 59/64")	2.073 m (6'-9 39/64")	30,000 kg (66,140 lb)	2,790 kg (6,150 lb)	27,210 kg (59,990 lb)	20'-0" 6.058 m	8'-0" 2.438 m	8'-6" 2.591 m	18'-5 62/64" 5.638 m	7'-3 46/64" 2.228 m	7'-3 59/64" 2.233 m	74,950 lb 34,000 kg	6,370 lb 2,890 kg	68,580 lb 31,110 kg
40呎角柱可折疊式之床式/平台兩用貨櫃																	
UGMU707001~ UGMU707050; EMCU700251~EMCU700450																	
40呎前後板框可折疊式之床式/平台兩用貨櫃																	
EISU710000~ EISU710500; EMCU700451~ EMCU700650																	
外部尺寸			內部尺寸			重量限制			外部尺寸			內部尺寸			重量限制		
長	寬	高	長	寬	高	總重	空櫃重	貨物淨重	長	寬	高	長	寬	高	總重	空櫃重	貨物淨重
40'-0" 12.192 m	8'-0" 2.438 m	8'-6" 2.591 m	38'-7 15/16" 11.784 m	6'-7 59/64" 2.030 m	6'-4 1/2" 1.943 m	99,210 lb 45,000 kg	11,908 lb 5,400 kg	87,302 lb 39,600 kg	40'-0" 12.192 m	8'-0" 2.438 m	8'-6" 2.591 m	38'-7 39/64" 11.776 m	7'-3 46/64" 2.228 m	6'-4 61/64" 1.955 m	99,210 lb 45,000 kg	10,140 lb 4,600 kg	89,407 lb 40,400 kg

您想深入瞭解海運貨櫃如何平衡堆積與船邊如何固定(LASHING)作業時，請來電聯絡，我們會有專人講解。

<http://ndlii.com> 恩得利網路報關系統04-22620983永遠提供您最好的服務 + 便宜30%收費