

# 長榮海運貨櫃規格明細表

非長榮之貨櫃規格 請另洽詢所屬船公司

| 海運材積單位換算: 1立方公尺(CBM)(M³)=35.315英材(立方英尺)(CU.FT), 1英材(立方英尺)(CU.FT)=1728立方英吋(CU.IN) |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
|--|---------------------|--------------------|--------------------------|----------------------------|--------------------------|---|---|--------------------------|-------------------------|--------------------------|-----------------------|-------------------------|-------------|-------------|--------------------------|-------------------------|--------------------------|
| 貨櫃類別   | 外部尺寸                |                    |                          | 內部尺寸                       |                          |   | 重量限制                                    |                          |                         |                          | 櫃門內徑                  |                         |             |             |                          |                         |                          |
|  | 長                   | 寬                  | 高                        | 長                          | 寬                        | 高   | 總重                                      | 空櫃重                      | 貨物淨重                    | 內容積                      | 寬                     | 高                       |             |             |                          |                         |                          |
| <b>20呎鋼製乾貨貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.898m<br>(19'-4 13/16")   | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 24,000kg<br>(52,910 lb)                 | 2,330kg<br>(5,140 lb)    | 21,670kg<br>(47,770 lb) | 33.1cbm<br>(1,169cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.280m<br>(7'-5 3/4")   |             |             |                          |                         |                          |
| 總重為 30,480 KG 之 20呎貨櫃櫃號始於 EMCU 3204073 及 EISU 3568118。                           |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎鋼製乾貨貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 12.032m<br>(39'-5 45/64")  | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 30,480kg<br>(67,200 lb)                 | 4,000kg<br>(8,820 lb)    | 26,480kg<br>(58,380 lb) | 67.5cbm<br>(2,385cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.280m<br>(7'-5 3/4")   |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋼製乾貨貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 12.032m<br>(39'-5 45/64")  | 2.352m<br>(7'-8 19/32")  | 2.69m<br>(8'-9 15/16")                              | 30,480kg<br>(67,200 lb)                 | 4,200kg<br>(9,260 lb)    | 26,280kg<br>(57,940 lb) | 76.2cbm<br>(2,690cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.585m<br>(8'-5 49/64") |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(1)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 30,480kg<br>(67,200 lb)                 | 4,800kg<br>(10,580 lb)   | 25,680kg<br>(56,620 lb) | 86.1cbm<br>(3,040cu.ft)  | 2.340m<br>(7'-8 1/8") | 2.585m<br>(8'-5 3/4")   |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(2)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 30,480kg<br>(67,200 lb)                 | 4,870kg<br>(10,858 lb)   | 25,610kg<br>(56,342 lb) | 86cbm<br>(3,040cu.ft)    | 2.340m<br>(7'-8 1/8") | 2.585m<br>(8'-5 3/4")   |             |             |                          |                         |                          |
| EISU 804001~EISU 804500; EMCU 801001~EMCU 802500                                 |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(3)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 32,500kg<br>(71,650 lb)                 | 4,700kg<br>(10,360 lb)   | 27,800kg<br>(61,290 lb) | 86cbm<br>(3,040cu.ft)    | 2.340m<br>(7'-8")     | 2.585m<br>(8'-6")       |             |             |                          |                         |                          |
| EISU 802001~EISU 804000 2. 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。                         |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高成衣櫃</b>  | 12.19m<br>(40'-0")  | 2.44m<br>(8'-0")   | 2.90m<br>(9'-6")         | 12.03m<br>(39'-5 45/64")   | 2.35m<br>(7'-8 19/32")   | 2.69m<br>(8'-9 15/16")                              | 30,480kg<br>(67,200 lb)                 | 4,200kg<br>(9,172 lb)    | 26,280kg<br>(58,028 lb) |                          | 2.343m<br>(7'-8 1/8") | 2.585m<br>(8'-5 49/64") |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎油槽櫃</b>  | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        |                            |                          |   | 6,000kg <sup>3</sup>                    | 3,385kg                  | 32,615kg                | 24,000litres             | 工作溫度                  |                         |             |             |                          |                         |                          |
| 上述油槽櫃僅用於集團屬輪上，做為貨櫃式發電機之供油使用，不對外營運。   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| -20°C to 130°C   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎全高開頂貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.59m<br>(8'-6")         | 5.898m<br>(19'-4")         | 2.352m<br>(7'-8 1/2")    | 2.342m<br>(7'-8 1/8")                               | 20,320kg<br>(44,800 lb)                 | 2,200kg<br>(4,850 lb)    | 18,120kg<br>(39,950 lb) | 32.5cbm<br>(1,148cu.ft)  |                       |                         |             |             |                          |                         |                          |
| UGMU 490001~UGMU 490150, EMCU 460261~EMUC 460520, EISU 460001~EISU 460400        |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎全高開頂貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 12.034m<br>(39'-5")        | 2.352m<br>(7'-8 1/2")    | 2.330m<br>(7'-8 1/8")                               | 30,480kg<br>(67,200 lb)                 | 4,100kg<br>(9,040 lb)    | 26,380kg<br>(58,160 lb) | 65.9cbm<br>(2,327cu.ft)  |                       |                         |             |             |                          |                         |                          |
| EMCU400362~400810; UGMU407001~407050; EISU400001~400600                          |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎貨櫃式發電機櫃</b>  | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.898m<br>(19'-4 13/16")   | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 8,500kg                                 | 2,400kg                  | 6,100kg                 |                          | 供電量:450kw             |                         |             |             |                          |                         |                          |
| 上述發電機僅用於集團屬輪上，供應冷凍櫃插電使用，不對外營運。   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 插座數:40   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎鋼製冷凍貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.500m<br>(18'- 17/32")    | 2.298m<br>(7'-6 15/32")  | 2.276m<br>(7'-5 39/54")                             | 30,480kg<br>(67,180 lb)                 | 3,020kg<br>(6,700 lb)    |                         | 28.8cbm<br>(1,016 cu.ft) | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   | 10,550(9,073)/2(35)6,150(5,289)-18(0)   |                          |                         |                          | 0-240                 | +0.25C                  |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎鋁製冷凍貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.480m<br>(17'-0")         | 2.286m<br>(7'-6")        | 2.235m<br>(7'-3")                                   | 24,000kg<br>(52,800 lb)                 | 2,800kg<br>(6,170 lb)    |                         | 28cbm<br>(989cu.ft)      | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋼製冷凍貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 11.585m<br>(37'-11 55/64") | 2.290m<br>(7'-6 15/32")  | 2.544m<br>(8'-4 5/32")                              | 34,000kg<br>(74,960 lb)                 | 4,760kg<br>(10,490lb)    |                         | 67.5cbm<br>(2,384cu.ft)  | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   | 10,550(9,073)/2(35)6,150(5,289)-18(0)   |                          |                         |                          | 0-240                 | +0.25C                  |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋁製冷凍貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 11.563m<br>(37'-11")       | 2.286m<br>(7'-6")        | 2.5047m<br>(8'-2")                                  | 30,480kg<br>(67,200 lb)                 | 4,300kg<br>(9,480 lb)    |                         | 66.27cbm<br>(2,340)      | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎角柱可折疊式之床式/平台兩用貨櫃(EMCU760321~EMCU760520)</b>                                |                     |                    |                          |                            |                          | <b>20呎前後板框可折疊式之床式/平台兩用貨櫃(EISU750000~EISU750300)</b> |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 外部尺寸   |                     |                    | 內部尺寸                     |                            |                          | 重量限制  |   |                          | 外部尺寸                    |                          |                       | 內部尺寸                    |             |             | 重量限制                     |                         |                          |
| 長  | 寬                   | 高                  | 長                        | 寬                          | 高                        | 總重  | 空櫃重                                     | 貨物淨重                     | 長                       | 寬                        | 高                     | 長                       | 寬           | 高           | 總重                       | 空櫃重                     | 貨物淨重                     |
| 6.058 m<br>(20'-0")  | 2.438 m<br>(8'-0")  | 2.591 m<br>(8'-6") | 5.650 m<br>(18'-6 7/16") | 2.030 m<br>(6'-7 59/64")   | 2.073 m<br>(6'-9 39/64") | 30,000 kg<br>(66,140 lb)                            | 2,790 kg<br>(6,150 lb)                  | 27,210 kg<br>(59,990 lb) | 20'-0"                  | 8'-0"                    | 8'-6"                 | 18'-5 62/64"            | 7'-3 46/64" | 7'-3 59/64" | 74,950 lb<br>(34,000 kg) | 6,370 lb<br>(2,890 kg)  | 68,580 lb<br>(31,110 kg) |
| <b>40呎角柱可折疊式之床式/平台兩用貨櫃</b>   |                     |                    |                          |                            |                          | <b>40呎前後板框可折疊式之床式/平台兩用貨櫃</b>                        |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| UGMU707001~ UGMU707050; EMCU700251~EMCU700450                                    |                     |                    |                          |                            |                          | EISU710000~ EISU710500, EMCU700451~ EMCU700650      |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 外部尺寸   |                     |                    | 內部尺寸                     |                            |                          | 重量限制  |   |                          | 外部尺寸                    |                          |                       | 內部尺寸                    |             |             | 重量限制                     |                         |                          |
| 長  | 寬                   | 高                  | 長                        | 寬                          | 高                        | 總重  | 空櫃重                                     | 貨物淨重                     | 長                       | 寬                        | 高                     | 長                       | 寬           | 高           | 總重                       | 空櫃重                     | 貨物淨重                     |
| 40'-0"   | 8'-0"               | 8'-6"              | 38'-7 15/16"             | 6'-7 59/64"                | 6'-4 1/2"                | 99,210 lb<br>(45,000 kg)                            | 11,908 lb<br>(5,400 kg)                 | 87,302 lb<br>(39,600 kg) | 40'-0"                  | 8'-0"                    | 8'-6"                 | 38'-7 39/64"            | 7'-3 46/64" | 6'-4 61/64" | 99,210 lb<br>(45,000 kg) | 10,140 lb<br>(4,600 kg) | 89,407 lb<br>(40,400 kg) |

您想深入瞭解海運貨櫃如何平衡堆積與船邊如何固定(LASHING)作業時，請來電聯絡，我們會有專人講解。

<http://ndlii.com> 恩得利網路報關系統04-22620983永遠提供您最好的服務 + 便宜30%收費

# 長榮海運貨櫃規格明細表

非長榮之貨櫃規格 請另洽詢所屬船公司

| 海運材積單位換算: 1立方公尺(CBM)(M³)=35.315英材(立方英尺)(CU.FT), 1英材(立方英尺)(CU.FT)=1728立方英吋(CU.IN) |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
|--|---------------------|--------------------|--------------------------|----------------------------|--------------------------|---|---|--------------------------|-------------------------|--------------------------|-----------------------|-------------------------|-------------|-------------|--------------------------|-------------------------|--------------------------|
| 貨櫃類別   | 外部尺寸                |                    |                          | 內部尺寸                       |                          |   | 重量限制                                    |                          |                         |                          | 櫃門內徑                  |                         |             |             |                          |                         |                          |
|  | 長                   | 寬                  | 高                        | 長                          | 寬                        | 高   | 總重                                      | 空櫃重                      | 貨物淨重                    | 內容積                      | 寬                     | 高                       |             |             |                          |                         |                          |
| <b>20呎鋼製乾貨貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.898m<br>(19'-4 13/16")   | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 24,000kg<br>(52,910 lb)                 | 2,330kg<br>(5,140 lb)    | 21,670kg<br>(47,770 lb) | 33.1cbm<br>(1,169cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.280m<br>(7'-5 3/4")   |             |             |                          |                         |                          |
| 總重為 30,480 KG 之 20呎貨櫃櫃號始於 EMCU 3204073 及 EISU 3568118。                           |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎鋼製乾貨貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 12.032m<br>(39'-5 45/64")  | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 30,480kg<br>(67,200 lb)                 | 4,000kg<br>(8,820 lb)    | 26,480kg<br>(58,380 lb) | 67.5cbm<br>(2,385cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.280m<br>(7'-5 3/4")   |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋼製乾貨貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 12.032m<br>(39'-5 45/64")  | 2.352m<br>(7'-8 19/32")  | 2.69m<br>(8'-9 15/16")                              | 30,480kg<br>(67,200 lb)                 | 4,200kg<br>(9,260 lb)    | 26,280kg<br>(57,940 lb) | 76.2cbm<br>(2,690cu.ft)  | 2.343m<br>(7'-8 1/8") | 2.585m<br>(8'-5 49/64") |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(1)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 30,480kg<br>(67,200 lb)                 | 4,800kg<br>(10,580 lb)   | 25,680kg<br>(56,620 lb) | 86.1cbm<br>(3,040cu.ft)  | 2.340m<br>(7'-8 1/8") | 2.585m<br>(8'-5 3/4")   |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(2)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 30,480kg<br>(67,200 lb)                 | 4,870kg<br>(10,858 lb)   | 25,610kg<br>(56,342 lb) | 86cbm<br>(3,040cu.ft)    | 2.340m<br>(7'-8 1/8") | 2.585m<br>(8'-5 3/4")   |             |             |                          |                         |                          |
| EISU 804001~EISU 804500; EMCU 801001~EMCU 802500                                 |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>45呎超高鋼製乾貨貨櫃(3)</b>  | 13.716m<br>(45'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 13.556m<br>(44'-5 7/10")   | 2.352m<br>(7'-8 19/32")  | 2.698m<br>(8'-10 17/64")                            | 32,500kg<br>(71,650 lb)                 | 4,700kg<br>(10,360 lb)   | 27,800kg<br>(61,290 lb) | 86cbm<br>(3,040cu.ft)    | 2.340m<br>(7'-8")     | 2.585m<br>(8'-6")       |             |             |                          |                         |                          |
| EISU 802001~EISU 804000 2. 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。                         |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高大衣櫃</b>  | 12.19m<br>(40'-0")  | 2.44m<br>(8'-0")   | 2.90m<br>(9'-6")         | 12.03m<br>(39'-5 45/64")   | 2.35m<br>(7'-8 19/32")   | 2.69m<br>(8'-9 15/16")                              | 30,480kg<br>(67,200 lb)                 | 4,200kg<br>(9,172 lb)    | 26,280kg<br>(58,028 lb) |                          | 2.343m<br>(7'-8 1/8") | 2.585m<br>(8'-5 49/64") |             |             |                          |                         |                          |
| 上述資料僅供參考，實際尺寸及重量應以各櫃櫃體所標示者為準。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎油槽櫃</b>  | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        |                            |                          |   | 6,000kg <sup>3</sup>                    | 3,385kg                  | 32,615kg                | 24,000litres             | 工作溫度                  |                         |             |             |                          |                         |                          |
| 上述油槽櫃僅用於集團屬輪上，做為貨櫃式發電機之供油使用，不對外營運。   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| -20°C to 130°C   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎全高開頂貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.59m<br>(8'-6")         | 5.898m<br>(19'-4")         | 2.352m<br>(7'-8 1/2")    | 2.342m<br>(7'-8 1/8")                               | 20,320kg<br>(44,800 lb)                 | 2,200kg<br>(4,850 lb)    | 18,120kg<br>(39,950 lb) | 32.5cbm<br>(1,148cu.ft)  |                       |                         |             |             |                          |                         |                          |
| UGMU 490001~UGMU 490150, EMCU 460261~EMUC 460520, EISU 460001~EISU 460400        |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎全高開頂貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 12.034m<br>(39'-5")        | 2.352m<br>(7'-8 1/2")    | 2.330m<br>(7'-8 1/8")                               | 30,480kg<br>(67,200 lb)                 | 4,100kg<br>(9,040 lb)    | 26,380kg<br>(58,160 lb) | 65.9cbm<br>(2,327cu.ft)  |                       |                         |             |             |                          |                         |                          |
| EMCU400362~400810; UGMU407001~407050; EISU400001~400600                          |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎貨櫃式發電機櫃</b>  | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.898m<br>(19'-4 13/16")   | 2.352m<br>(7'-8 19/32")  | 2.385m<br>(7'-9 57/64")                             | 8,500kg                                 | 2,400kg                  | 6,100kg                 |                          | 供電量:450kw             |                         |             |             |                          |                         |                          |
| 上述發電機僅用於集團屬輪上，供應冷凍櫃插電使用，不對外營運。   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 插座數:40   |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎鋼製冷凍貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.500m<br>(18'-17/32")     | 2.298m<br>(7'-6 15/32")  | 2.276m<br>(7'-5 39/64")                             | 30,480kg<br>(67,180 lb)                 | 3,020kg<br>(6,700 lb)    |                         | 28.8cbm<br>(1,016 cu.ft) | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   | 10,550(9,073)/2(35)6,150(5,289)-18(0)   |                          |                         |                          | 0-240                 | +0.25C                  |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎鋁製冷凍貨櫃</b>   | 6.058m<br>(20'-0")  | 2.438m<br>(8'-0")  | 2.591m<br>(8'-6")        | 5.480m<br>(17'-0")         | 2.286m<br>(7'-6")        | 2.235m<br>(7'-3")                                   | 24,000kg<br>(52,800 lb)                 | 2,800kg<br>(6,170 lb)    |                         | 28cbm<br>(989cu.ft)      | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋼製冷凍貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 11.585m<br>(37'-11 55/64") | 2.290m<br>(7'-6 15/32")  | 2.544m<br>(8'-4 5/32")                              | 34,000kg<br>(74,960 lb)                 | 4,760kg<br>(10,490lb)    |                         | 67.5cbm<br>(2,384cu.ft)  | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   | 10,550(9,073)/2(35)6,150(5,289)-18(0)   |                          |                         |                          | 0-240                 | +0.25C                  |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>40呎超高鋁製冷凍貨櫃</b>   | 12.192m<br>(40'-0") | 2.438m<br>(8'-0")  | 2.896m<br>(9'-6")        | 11.563m<br>(37'-11")       | 2.286m<br>(7'-6")        | 2.5047m<br>(8'-2")                                  | 30,480kg<br>(67,200 lb)                 | 4,300kg<br>(9,480 lb)    |                         | 66.27cbm<br>(2,340)      | 設溫之容許誤差               |                         |             |             |                          |                         |                          |
|  | 製冷能力:瓦(千卡)/攝氏(華氏)   |                    |                          |                            |                          |   | 11,000(9,460)/1.7(35)6,280(5,400)-18(0) | 通風量:立方公尺/小時              |                         |                          | 0-180                 | +0.25C                  |             |             |                          |                         |                          |
|  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 此為設計內部容積，實際貨物裝載仍應低於櫃內貨物線，以利冷空氣循環。  |                     |                    |                          |                            |                          |   |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| <b>20呎角柱可折疊式之床式/平台兩用貨櫃(EMCU760321~EMCU760520)</b>                                |                     |                    |                          |                            |                          | <b>20呎前後板框可折疊式之床式/平台兩用貨櫃(EISU750000~EISU750300)</b> |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 外部尺寸   |                     |                    | 內部尺寸                     |                            |                          | 重量限制  |   |                          | 外部尺寸                    |                          |                       | 內部尺寸                    |             |             | 重量限制                     |                         |                          |
| 長  | 寬                   | 高                  | 長                        | 寬                          | 高                        | 總重  | 空櫃重                                     | 貨物淨重                     | 長                       | 寬                        | 高                     | 長                       | 寬           | 高           | 總重                       | 空櫃重                     | 貨物淨重                     |
| 6.058 m<br>(20'-0")  | 2.438 m<br>(8'-0")  | 2.591 m<br>(8'-6") | 5.650 m<br>(18'-6 7/16") | 2.030 m<br>(6'-7 59/64")   | 2.073 m<br>(6'-9 39/64") | 30,000 kg<br>(66,140 lb)                            | 2,790 kg<br>(6,150 lb)                  | 27,210 kg<br>(59,990 lb) | 20'-0"                  | 8'-0"                    | 8'-6"                 | 18'-5 62/64"            | 7'-3 46/64" | 7'-3 59/64" | 74,950 lb<br>(34,000 kg) | 6,370 lb<br>(2,890 kg)  | 68,580 lb<br>(31,110 kg) |
| <b>40呎角柱可折疊式之床式/平台兩用貨櫃</b>   |                     |                    |                          |                            |                          | <b>40呎前後板框可折疊式之床式/平台兩用貨櫃</b>                        |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| UGMU707001~ UGMU707050; EMCU700251~EMCU700450                                    |                     |                    |                          |                            |                          | EISU710000~ EISU710500, EMCU700451~ EMCU700650      |   |                          |                         |                          |                       |                         |             |             |                          |                         |                          |
| 外部尺寸   |                     |                    | 內部尺寸                     |                            |                          | 重量限制  |   |                          | 外部尺寸                    |                          |                       | 內部尺寸                    |             |             | 重量限制                     |                         |                          |
| 長  | 寬                   | 高                  | 長                        | 寬                          | 高                        | 總重  | 空櫃重                                     | 貨物淨重                     | 長                       | 寬                        | 高                     | 長                       | 寬           | 高           | 總重                       | 空櫃重                     | 貨物淨重                     |
| 40'-0"   | 8'-0"               | 8'-6"              | 38'-7 15/16"             | 6'-7 59/64"                | 6'-4 1/2"                | 99,210 lb<br>(45,000 kg)                            | 11,908 lb<br>(5,400 kg)                 | 87,302 lb<br>(39,600 kg) | 40'-0"                  | 8'-0"                    | 8'-6"                 | 38'-7 39/64"            | 7'-3 46/64" | 6'-4 61/64" | 99,210 lb<br>(45,000 kg) | 10,140 lb<br>(4,600 kg) | 89,407 lb<br>(40,400 kg) |

您想深入瞭解海運貨櫃如何平衡堆積與船邊如何固定(LASHING)作業時，請來電聯絡，我們會有專人講解。

<http://ndlii.com> 恩得利網路報關系統04-22620983永遠提供您最好的服務 + 便宜30%收費